Ultimaker

Safety data sheet PLA

1. Identification of the substance / preparation and of the company

1.1 Trade name PLA

1.2 Use of the product 3D printer filament

1.3 Supplier Ultimaker B.V.

Watermolenweg 2 4191 PN, Geldermalsen

The Netherlands

Emergency phone number In case of toxicological emergency, contact your doctor

2. Hazards identification according to regulation (EC) No 1272/2008 and GHS

2.1 Classification of the substance or mixture No risk exists to the health of users if the product is

handled and processed properly

2.2 Label elements Not applicable2.3 Other hazards Not known

3. Composition / information on ingredients

3.1 Composition Polylactic acid
3.2 Mixture Not applicable

4. First-aid measures

4.1 Description of first-aid measures

General advice If you feel unwell, seek medical advice (show the label where

possible). Never give anything by mouth to an unconscious

person

Inhalation In case of inhalation of gases released from molten filament,

move person into fresh air

Skin contact Wash with soap and water. Seek medical attention if symptoms

occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water – do not try to peel it off. Seek for medical attention, if necessary, for

removal and treatment of the burns

Eye contact Any material that contacts the eye should be washed out

immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at

least 15 minutes. Seek medical attention immediately

Ingestion Not probable. Seek medical advice in case ingestion occurs

Note to physician Treat symptomatically

4.2 Most important symptoms and effects, both acute and delayed

Burns should be treated as thermal burns. The material will come off as healing occurs; therefore immediate removal from skin is not necessary

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. Firefighting measures

5.1 General advice Material can accumulate static charges which may cause an

electrical spark (ignition source). Use proper bonding and/or

grounding procedures

5.2 Extinguishing media Foam, carbon dioxide (CO₂), water, dry chemical. Alcohol

resistant foams are preferred if available. General purpose synthetic foams (including AFFF) or protein foams may function,

but are much less effective

Unsuitable extinguishing media: not known

5.3 Special hazards arising from the

substance or mixture

Burning produces unpleasant and toxic fumes: carbon oxides

(CO_x) and aldehydes

5.4 Advice for firefighters Use self-contained breathing apparatus and full protective

clothing

6. Accidental release measures

6.1 Personal precautions, protectiveequipment, and emergency procedures
adequate ventilation, especially in confined areas

6.2 Environmental precautionsNo data available

6.3 Methods and materials for containment

and cleaning up

Allow to solidify molten material. Dispose of waste and residue

according to local regulations

6.4 Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling Avoid contact with molten material

7.2 Conditions for safe storage, including any incompatibilities

Product should be stored in a dry and cool place at temperatures between -20 to +30 °C. Avoid direct sunlight. Minimize moisture uptake by leaving it in a sealed package together with the

supplied desiccant

7.3 Specific end use(s) Filament for 3D printing

8. Exposure controls / personal protection

8.1 Control parameters None

DNEL No data available
PNEC No data available

8.2 Exposure controls

Eye protection Use safety glasses for prolonged staring at printing

Skin and body protection Good practices suggest to minimize skin contact. When material

is heated, wear gloves to protect against thermal burns

Respiratory protection If engineering controls do not maintain airborne concentrations

below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be used. Respirator type: air-purifying respirator with an appropriate government-approved (where applicable) air-purifying filter, cartridge, or canister. Contact a health and safety professional or

manufacturer for specific information

Hand protection Follow good industrial hygiene practices Hygiene measures Follow good industrial hygiene practices

Engineering measures Good general ventilation (typically 10 air changes per hour)

is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Filament **Appearance**

Color Various (incl. transparent)

Odor Slight

Flash point

388 °C Ignition temperature 250 °C Thermal decomposition

Auto-ignition temperature

145 - 160 °C Melting point / range Density 1.24 g/cm³ Insoluble

Solubility in other solvents Chloroform smoothable

9.2 Other information

10. Stability

Water solubility

Stable under recommended storage conditions

10.1 Reactivity No data available 10.2 Chemical stability Biodegradable

10.3 Possibility of hazardous reactions No decomposition or hazardous reactions if stored and applied

as directed

10.4 Conditions to avoid Print temperatures above 240 °C (at standard printing speeds)

10.5 Incompatible materials Oxidizing agents, strong bases

10.6 Hazardous decomposition products See 5.2

11. Toxicological information

11.1 Information on toxicological effects

Principal routes of exposure Eye contact, skin contact, inhalation, ingestion

Acute toxicity There were no target organ effects noted following ingestion or

dermal exposure in animal studies

Skin corrosion / irritation May cause eye / skin irritation. Product dust may be irritating

to eyes, skin, and respiratory system. Caused mild to moderate conjunctival irritation in eye irritation studies using rabbits. Caused very mild redness in dermal irritation studies using

rabbits (slightly irritating)

Serious eye damage / eye irritation No data available
Respiratory or skin sensitization No data available
Reproductive toxicity No data available
Carcinogenicity No data available

12. Ecological information

12.1 Toxicity No data available

12.2 Persistence and degradability -

12.3 Bio accumulative potential Does not bio accumulate

12.4 Mobility in soilNo data available12.5 Results of PBT and vPvB assessmentNo data available12.6 Other adverse effectsNo data available

13. Disposal considerations

13.1 Waste treatment methods In accordance with local and national regulations

14. Transport information

ADR Not regulated RID Not regulated IATA Not regulated IMDG Not regulated

Special precautions for user -

15. Regulatory information

Not meant to be all-inclusive — selected regulations represented

15.1 Safety, health, and environmental regulations / legislation specific for the substance or mixture

US Regulations:

Sara 313 title III Not listed
TSCA Inventory List Listed

OSHA hazard category CERCLA -

WHMIS -

State right-to-know requirements -

Other Inventories:

Canada DSL Inventory List Listed

REACH / EU EINIECS Components are in compliance with REACH and/or are listed

NEHAPS -

Japan (ECL/MITI)

Australia (AICS)

Korean toxic substances control act (ECL)

Philippines inventory (PICCS)

Chinese chemical inventory (IECSC)

Listed

Listed

15.2 Chemical Safety Assessment No data available

16. Other information

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

Version Version 4.002

Date January 14, 2019